

WAX PRO | TECHNICAL DATA SHEET

DESCRIPTIONS

A unique wax based composition specially formulated to provide long-term protection for all metal surfaces from moisture, oxidation, rust & corrosion. It is a mixture of high performance new generation rust, corrosion & oxidation inhibitors blended is a highly stable medium.

APPLICATIONS

The product provides long-term protection from rust & corrosion to metal parts, tools, dies,

moulds, equipment, fittings, valves, pipes etc, up to twelve months period. It is extremely

suitable for protection of moulds & dies of Plastic Moulding Industries.

PRECAUTIONS

Can is under high pressure. Do not puncture or incinerate it even when apparently empty. Store below 50 °C. Use in well ventilated areas. Do no spray into or around open flames and sparks. Exposure to heat, which exceeds 120 °C, may cause busting of the can. Keep out of reach of children.

ANTI-CORROSIVE WAX COATING GREEN IN COLOR EASY REMOVAL NO SURFACE DISCOLOURATION

PRODUCT IDENTIFICATION

The product is made in two colors i.e. clear amber and bright green, which allows quickidentification of the area covered. When sprayed it forms an oily film, which is safe on all metals, plastic, rubber and painted surfaces. This can be removed by a hydrocarbon degreaser.

GOVERNING SPECIFICATIONS

Has been formulated keeping is view the stringent requirements of Defence Forces. It meets U.S. Military specifications MIL- C - 23411 A.

PHYSICAL-CHEMICAL PROPERTIES

• Appearance: Tacky Wax Coating

• Color: Clear / Green

• Density: 0.87

Flash Point: > 80 °CPour Point: (-) 20 °C

• Corrosion Protection Test: Passes 200 hrs. (ASTM B 117)

Important: The information given this literature is true and reliable, and based on the Physical and the Chemical properties data of the basic raw materials used by us, to the best of our knowledge. Users are advised to make their own assessments regarding the authenticity and usability and findings on applications prior to the use of these products. The manufacturer's liability is limited to the extent of replacement of the defective materials. The manufacturers shall not be responsible for operations not under their direct control.